



## Technical Specifications

Product Code	Size (Inch)	Tighten Range D(mm)	Material Dimension (bxs)	Hanging Nuts (A)	SW	H	L	Breaking Load (kN)	Recommended Load (kN)	Connection Screw (C)
2S N - 01	1/4"	12-15	1,5x20	M8	13	26,5	56	3,9	1	M6x18
2S N - 02	3/8"	15-19	1,5x20	M8	13	29	60	3,9	1	M6x18
2S N - 03	1/2"	20-24	1,5x20	M8	13	33,5	62	3,9	1	M6x18
2S N - 04	3/4"	23-28	1,5x20	M8	13	39	70,5	3,9	1	M6x18
2S N - 05	1"	31-36	1,5x20	M8	13	49,5	79	3,9	1,3	M6x18
2S N - 06	1 1/4"	38-44	1,5x20	M8	13	53,5	88	4,8	1,3	M6x18
2S N - 07	1 1/2"	44-50	1,5x20	M8	13	59	94	4,8	1,3	M6x18
2S N - 08	-	54-58	1,5x20	M8	13	67,5	102	4,8	1,3	M6x18
2S N - 09	2"	59-65	1,5x20	M8	13	76	109	4,8	1,3	M6x18
2S N - 10	-	62-67	1,5x20	M8	13	78,5	115	4,8	2	M6x18
2S N - 11	2 1/2"	74-80	2x25	M10	17	97	133	6,9	2	M6x25
2S N - 12	3"	83-93	2x25	M10	17	106	145	6,9	2	M6x25
2S N - 13	-	95-103	2x25	M10	17	116	154	6,9	2	M6x25
2S N - 14	4"	108-118	2x25	M10	17	131	169	6,9	2	M6x25
2S N - 15	-	121-127	2x25	M10	17	140	178	6,9	2	M6x25
2S N - 16	5"	132-143	2x25	M10	17	156	198,5	6,9	2	M6x25
2S N - 17	6"	159-169	2x25	M10	17	184	229	7,8	2,5	M6x25
2S N - 18	-	198-202	2x25	M10	17	215	253	7,8	2,5	M6x25
2S N - 19	-	210-215	2x25	M10	17	228	266	7,8	2,5	M6x25
2S N - 20	8"	216-225	2x25	M10	17	234	283	7,8	2,5	M6x25