



Technical Specifications

Product Code	Size (Inch)	Tighten Range D(mm)	Material Dimension (bxs)	Hanging Nuts (A)	SW	H	L	Breaking Load (kN)	Recommended Load (kN)	Connection Screw (C)
2S CN - 01	1/4"	12-15	1,5x20	M8/M10	13	38	56	3	0,8	M6x18
2S CN - 02	3/8"	15-19	1,5x20	M8/M10	13	40,5	60	3	0,8	M6x18
2S CN - 03	1/2"	20-24	1,5x20	M8/M10	13	45	62	3	0,8	M6x18
2S CN - 04	3/4"	23-28	1,5x20	M8/M10	13	49,5	70,5	3	0,8	M6x18
2S CN - 05	1"	31-36	1,5x20	M8/M10	13	60	79	3	1	M6x18
2S CN - 06	1 1/4"	38-44	1,5x20	M8/M10	13	64	88	3	1	M6x18
2S CN - 07	1 1/2"	44-50	1,5x20	M8/M10	13	70,5	94	3	1	M6x18
2S CN - 08	-	54-58	1,5x20	M8/M10	13	81,5	102	3	1	M6x18
2S CN - 09	2"	59-65	1,5x20	M8/M10	13	86,5	109	3	1	M6x18
2S CN - 10	-	62-67	1,5x20	M8/M10	13	88,5	120	3	1	M6x18
2S CN - 11	2 1/2"	74-80	2x25	M8/M10	13	102,5	133	3,5	1,5	M6x25
2S CN - 12	3"	83-93	2x25	M8/M10	13	111,5	145	3,5	1,5	M6x25
2S CN - 13	-	95-103	2x25	M8/M10	13	122	155	3,5	1,5	M6x25
2S CN - 14	4"	108-118	2x25	M8/M10	13	136,5	169	3,5	1,5	M6x25
2S CN - 15	-	121-127	2x25	M8/M10	13	145,5	178	3,5	1,5	M6x25
2S CN - 16	5"	132-143	2x25	M8/M10	13	161,5	198,5	3,5	1,5	M6x25
2S CN - 17	6"	159-169	2x25	M8/M10	13	189,5	229	3,5	1,5	M6x25
2S CN - 18	-	198-202	2x25	M8/M10	13	220,5	262	3,5	1,5	M6x25
2S CN - 19	-	210-215	2x25	M8/M10	13	230	275	3,5	1,5	M6x25
2S CN - 20	8"	216-225	2x25	M8/M10	13	239,5	283	3,5	1,5	M6x25